


SECTION C-C
SCALE 4X

D4-3
D4-4
D3-5
D3-6




DETAIL D
TYP, SCALE 4X


B5-3
B6-4
B3-5
B5-6

48179
RELEASED
09/07/13 MDD

DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	<i>RF</i>	DRAWING NO.	REV. B
MFG. APPR.	<i>RF</i>	D3847	SHEET 7 OF 7
APPROVED		TITLE	SCALE
DE APPR.	<i>RF</i>	WEARPLATE ASSY	NTS
DATE	09.06.30	<small>COPYRIGHT © 2008 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COMPILED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	



D3847-9 PLATE
MADE FROM D3847-9F FLAT PATTERN




D3847-9F FLAT PATTERN

48179
RELEASED
9/6/51

NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL PER AMS 5513 OR AMS 5524, 18 GAUGE (0.050 THICK), (REF. DART SPEC. M304S18GA)
- 2) FINISH: POWDER COAT "GREY SANTEX" (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 3.86 lbs


DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	PH	DRAWING NO. D3847	REV. B
MFG. APPR.	E	SHEET 6 OF 7	
APPROVED		TITLE	SCALE
DE APPR.	#	WEARPLATE ASSY	NTS
DATE	09.06.30	<small>COPYRIGHT © 2005 BY DART AEROSPACE USA, INC.</small> <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	



8 7 6 5 4 3 2 1

D


D



D3847-5 PLATE
MADE FROM D3847-5F FLAT PATTERN

C

C



D3847-5F FLAT PATTERN

48179

RELEASED
9/6/15/14

B


A

NOTES:



- 1) MATERIAL: AISI 304/316 STAINLESS STEEL PER AMS 5513 OR AMS 5524, 18 GAUGE (0.050 THICK), (REF. DART SPEC. M304S18GA)
- 2) FINISH: POWDER COAT "GREY SANDEX" (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 1.29 lbs

DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	RF	DRAWING NO. D3847	REV. B
MFG. APPR.	RF	SHEET 4 OF 7	
APPROVED	RF	TITLE	SCALE
DE APPR.	RF	WEARPLATE ASSY	NTS
DATE	09.06.30	<small>COPYRIGHT © 2009 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	

8 7 6 5 4 3 2 1



D3847-3 PLATE
MADE FROM D3847-3F FLAT PATTERN



D3847-3F FLAT PATTERN


NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL PER AMS 5513 OR AMS 5524, 18 GAUGE (0.050 THICK), (REF. DART SPEC. M304S18GA)
- 2) FINISH: POWDER COAT "GREY SANDING" (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 1.46 lbs


DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	RF	DRAWING NO.	REV. B
MFG. APPR.	RF	D3847	SHEET 3 OF 7
APPROVED	RF	TITLE	SCALE
DE APPR.	RF	WEARPLATE ASSY	NTS
DATE	09.06.30	COPYRIGHT © 2008 BY DART AEROSPACE USA, INC.	
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR DISCLOSED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.			

RELEASED
2/27/13


8 7 6 5 4 3 2 1




D3847-1 WEARPAD
MADE FROM D3847-1F FLAT PATTERN




D3847-1F FLAT PATTERN




SECTION A-A D7-2
B7-2



D3847-11 WEARPAD
MADE FROM D3847-11F FLAT PATTERN



D3847-11F FLAT PATTERN



DETAIL B C5-2
B5-2
TYP. SCALE 2X

NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL PER AMS 5513 OR AMS 5524, 16 GAUGE (0.063 THICK), (REF. DART SPEC. M304S16GA)
- 2) FINISH: POWDER COAT "GREY SANDTEX" (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3847-X" USING FINE POINT PERMANENT INK MARKER
- 7) WEIGHT:
D3847-1 = 0.03 lbs
D3847-11 = 0.47 lbs
- 8) WELD PER QSI 004
- 9) APPLY 2 LAYERS OF 2059B HARDCOAT WELDS TO WITHIN 0.25 OF WEARPAD ENDS 0.19 TO 0.25 THICK UNLESS OTHERWISE INDICATED





DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	<i>[Signature]</i>	DRAWING NO. D3847	REV. B
MFG. APPR.	<i>[Signature]</i>	SHEET 2 OF 7	
APPROVED	<i>[Signature]</i>	TITLE WEARPLATE ASSY	SCALE
DE APPR.	<i>[Signature]</i>	NTS	
DATE	09.06.30	<small>COPYRIGHT © 2009 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COME OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	

48179

RELEASED
11/29/07/154110

8 7 6 5 4 3 2 1

D3847-1 WEARPAD



ITEM	QTY -043	QTY -045	QTY -047	QTY -049	P/N	DESCRIPTION
1	X				D3847-043	FWD WEARPLATE ASSY, STD/FLOAT GEAR
2		X			D3847-045	CENTER WEARPLATE ASSY, STD/FLOAT GEAR
3			X		D3847-047	AFT WEARPLATE ASSY, STD GEAR
4				X	D3847-049	AFT WEARPLATE ASSY, FLOAT GEAR
11	1				D3847-3	PLATE
12		1			D3847-5	PLATE
13			1		D3847-7	PLATE
14				1	D3847-9	PLATE
15	1				D3846-3	GASKET
16		1			D3846-5	GASKET
17			1		D3846-7	GASKET
18				1	D3846-9	GASKET
31	A/R	A/R	A/R	A/R	1300 (OR 1300L)	3M SCOTCH-GRIP ADHESIVE

- NOTES:**
- 1) MATERIAL: N/A
 - 2) FINISH: NONE
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: N/A
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3847-XXX" USING YELLOW PAINT MARKER AT INSIDE SURFACE
 - 7) WEIGHT: D3847-043 = 1.71 lbs
D3847-045 = 1.49 lbs
D3847-047 = 2.00 lbs
D3847-049 = 4.21 lbs
 - 8) BOND D3846-X GASKET TO INNER SURFACE OF WEARPLATE USING A THIN LAYER OF 3M 1300/1300L SCOTCH GRIP ADHESIVE

D3847-11 WEARPAD

RELEASED
09/27/15

B	CORRECT TYPO D3847-047 WAS D3847-045, ZN B5-1; 5.82 WAS 6.25 (ZN A4-2); 45.28 WAS 45.71 (ZN B4-5)	RF	09.06.30
A	NEW ISSUE	RF	09.03.30
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE USA, INC. PORT HADLOCK, WA	
DRAWN	RF	DRAWING NO.	REV. B
CHECKED	RF	D3847	SHEET 1 OF 7
MFG. APPR.	RF	TITLE	SCALE
APPROVED	RF	WEARPLATE ASSY	NTS
DE APPR.	RF	COPYRIGHT © 2009 BY DART AEROSPACE USA, INC.	
DATE	09.06.30	THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSES OR COPIES OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector


Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____


NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries


8 7 6 5 4 3 2 1



D3847-1 WEARPAD
MADE FROM D3847-1F FLAT PATTERN




D3847-1F FLAT PATTERN




SECTION A-A D7-2
B7-2

PRELIMINARY ISSUE


#48179



D3847-11 WEARPAD
MADE FROM D3847-11F FLAT PATTERN



D3847-11F FLAT PATTERN



DETAIL B C5-2
TYP. SCALE 2X B5-2

NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL PER AMS 5513 OR AMS 5524, 16 GAUGE (0.063 THICK), (REF. DART SPEC. M304S16GA)
- 2) FINISH: POWDER COAT "GREY SANDTEX" (4.3.5.6) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D3847-X" USING FINE POINT PERMANENT INK MARKER
- 7) WEIGHT:
D3847-1 = 0.33 lbs
D3847-11 = 0.47 lbs
- 8) WELD PER QSI 004
- 9) APPLY 2 LAYERS OF 2059B HARDCOAT WELDS TO WITHIN 0.25 OF WEARPAD ENDS 0.19 TO 0.25 THICK UNLESS OTHERWISE INDICATED

DESIGN	RF	DART AEROSPACE USA, INC.	
DRAWN	RF	PORT HADLOCK, WA	
CHECKED	92	DRAWING NO.	REV. A
MFG. APPR.	15	D3847	SHEET 2 OF 7
APPROVED	140	TITLE	SCALE
DE APPR.	11	WEARPLATE ASSY	NTS
DATE	09.03.30	<small>COPYRIGHT © 2009 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	

8 7 6 5 4 3 2 1

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Monday, 25/05/2009 10:59:17 AM
User: Melanie Fauteux

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: WEARPAD

Job Number: 48179

Part Number: D38471

Job Number:



Seq. #:

Machine Or Operation:

Description :

13.0

QC21

FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



mf 09-06-08

POSITIVE RECALL

EFFECTIVE 09-05-25 AUTH 

RELEASED _____ DATE _____

ENG USE ONLY

09-08-02

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Monday, 25/05/2009 10:59:17 AM
User: Melanie Fauteux

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: WEARPAD

Job Number: 48179

Part Number: D38471

Job Number:



Seq. #:

Machine Or Operation:

Description :

6.0

QC5

INSPECT WORK TO CURRENT STEP



Comment: INSPECT WORK TO CURRENT STEP

Ensure joggle as per dwg D3429

7.0

LARGE FAB 1

LARGE FABRICATION RESOURCE 1



Comment: LARGE FABRICATION RESOURCE 1

Qty Description Batch
A/R 2059B Hardcoat

M111682

Weld hardcoat as per Dwg D3847

EL 9-6-3 (X6)

8.0

QC10

VISUAL INSPECTION OF GROUND WELDS



Comment: VISUAL INSPECTION OF GROUND WELDS

Inspected (B)

9.0

QC5

INSPECT WORK TO CURRENT STEP



Comment: INSPECT WORK TO CURRENT STEP

ENGINEERING APPROVAL

09.06.09

10.0

POWDER COATING

POWDER COATING



Comment: POWDER COATING

Powder Coat Grey Sandtex (Ref: 4.3.5.6) as per QSI 005 4.3

START TIME: 11:45am

OVEN TEMPERATURE: 320°F

FINISH TIME: 12:15pm

09-06-08 (X6)

11.0

QC3

INSPECT POWDER COAT/CHEMICAL CONVERSION



Comment: INSPECT POWDER COAT/CHEMICAL CONVERSION

09-06-08 (X6)

12.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: EP-17

09-06-08 (X6)

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

Resolution: _____ Disposition: _____ QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Monday, 25/05/2009 10:59:17 AM
User: Melanie Fauteux

Process Sheet

Customer	: CU-DAR001 Dart Helicopters Services	Drawing Name	: WEARPAD
Job Number	: 48179		
Estimate Number	: 13913		
P.O. Number	:	Part Number	: D38471
This Issue	: 25/05/2009 S.O. No. :	Drawing Number	: D3847 PREL
Prsht Rev.	: NC	Project Number	: N/A
First Issue	: / / Type : SMALL / MED FAB	Drawing Revision	: PREL
Previous Run	: 47808	Material	:
Written By	:	Due Date	: 01/06/2009 Qty: 4 Um: Each
Checked & Approved By	: <u>mf 09-05-25</u>		
Comment	: Est Rev:A New Issue 009.05.01 EC verified by:DD		

Additional Product

PRELIMINARY ISSUE

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

1.0	M304S16GA	304/316 Sheet .063
-----	-----------	--------------------



Comment: Qty.: 0.1260 sf(s)/Unit Total: 0.5040 sf(s)

M304S16GA Stainless steel sheet 0.063" thick

Batch: 111323 1B 9-5-25

2.0	WATER JET	FLOW WATER JET
-----	-----------	----------------



Comment: FLOW WATER JET

1-Cut as per Dwg D3847

Dwg Rev: PRE 1B 9-5-25Prog Rev: Lim2-Deburr if necessary 1B 9-5-25

3.0	QC2	INSPECT PARTS AS THEY COME OFF MACHINE
-----	-----	--



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

4.0	QC8	SECOND CHECK
-----	-----	--------------



ENGINEERING APPROVAL



Comment: SECOND CHECK

090522 (6)090527

5.0	BRAKE NC	NC BRAKE
-----	----------	----------



Comment: NC BRAKE

Deburr if necessary

Form on Brake as per Dwg D3847

SB 09/06/01(6)